

In r Patent Application of:  
CROCE ET AL.  
Serial No. 09/839,596  
Filing Date: APRIL 20, 2001

---

In the Claims:

This listing of claims replaces all prior versions  
and listing of claims in the application.

Claims 1-4 (Canceled).

5. (Previously presented) A lateral diffused metal  
oxide semiconductor (LDMOS) integrated device comprising:

a semiconductor substrate;

a drain region of a first conductivity type adjacent  
said semiconductor substrate and comprising a superficial  
buffer region being more heavily doped than adjacent portions  
of said drain region;

41 a body region completely surrounded on a bottom and  
sides thereof by said buffer region and having a second  
conductivity type; and

a source region in said body region and having the  
first conductivity type.

6. (Original) The LDMOS integrated device of Claim  
5 wherein said drain region has a depth of about 1.5 to 4.5  
micrometers.

7. (Original) The LDMOS integrated device of Claim  
5 wherein the portions of said drain region adjacent said  
superficial buffer region have a dopant concentration of about  
 $2.5 \times 10^{15}$  to  $2.5 \times 10^{16}$  atoms  $\text{cm}^{-3}$ .

In re Patent Application of:  
CROCE ET AL.  
Serial No. 09/839,596  
Filing Date: APRIL 20, 2001

---

8. (Original) The LDMOS integrated device of Claim 5 wherein said superficial buffer region has a depth of about 0.15 to 0.45 micrometers.

9. (Original) The LDMOS integrated device of Claim 5 wherein said superficial buffer region has a dopant concentration of about  $5 \times 10^{16}$  to  $5 \times 10^{17}$  atoms  $\text{cm}^{-3}$ .

E1  
Cm  
10. (Original) The LDMOS integrated device of Claim 5 wherein said body region has a depth of about 0.25 to 0.75 micrometers.

11. (Original) The LDMOS integrated device of Claim 5 wherein said body region has a dopant concentration of about  $5 \times 10^{17}$  to  $5 \times 10^{18}$  atoms  $\text{cm}^{-3}$ .

12. (Original) The LDMOS integrated device of Claim 5 wherein said drain region is doped with phosphorous; and wherein said body region is doped with boron.

13. (Original) The LDMOS integrated device of Claim 5 wherein said drain region is doped with boron; and wherein said body region is doped with phosphorus.

14. (Previously presented) A lateral diffused metal oxide semiconductor (LDMOS) integrated device comprising:  
a semiconductor substrate;  
a drain region of a first conductivity type adjacent said semiconductor substrate and comprising a superficial

BEST AVAILABLE COPY

In re Patent Application of:  
CROCE ET AL.  
Serial No. 09/839,596  
Filing Date: APRIL 20, 2001

buffer region being more heavily doped than adjacent portions of said drain region;

said superficial buffer region having a dopant concentration of about  $5 \times 10^{16}$  to  $5 \times 10^{17}$  atoms  $\text{cm}^{-3}$  and the adjacent portions of said drain region having a dopant concentration of about  $2.5 \times 10^{15}$  to  $2.5 \times 10^{16}$  atoms  $\text{cm}^{-3}$ ;

81  
end  
a body region completely surrounded on a bottom and sides thereof by said superficial buffer region and having a second conductivity type; and

a source region in said body region and having the first conductivity type.

15. (Original) The LDMOS integrated device of Claim 14 wherein said drain region has a depth of about 1.5 to 4.5 micrometers.

16. (Original) The LDMOS integrated device of Claim 14 wherein said buffer region has a depth of about 0.15 to 0.45 micrometers.

17. (Original) The LDMOS integrated device of Claim 14 wherein said body region has a depth of about 0.25 to 0.75 micrometers.

18. (Original) The LDMOS integrated device of Claim 14 wherein said body region has a dopant concentration of about  $5 \times 10^{17}$  to  $5 \times 10^{18}$  atoms  $\text{cm}^{-3}$ .

19-25. (Withdrawn).

BEST AVAILABLE COPY